

Fully compatible with HD audio and video. Featuring HD Audio decoding, HDMI (4 in/1 out), 1080p video upscaling, Pure Direct, YPAO, CINEMA DSP 3D and custom installation facility.




















- 7-channel powerful surround sound (630W=90W x 7. 805W=115W x 7)
- Decoders for HD audio formats: Dolby TrueHD and DTS-HD Master Audio: Dolby Digital Plus and DTS-HD High Resolution Audio
- Digital ToP-ART and High Current Amplification
- Pure Direct
- Burr-Brown 192 kHz/24-bit DACs for all channels
- Intelligent Assignable amplifiers for bi-amp or Surround Back <-> Front Presence or Zone 2 connection

High Picture Quality

- Analog video upscaling to full HD 1080p
- 1080p-compatible HDMI (4 in/1 out)
- Supports Deep Colour (30/36 bit), x.v.Colour, 120Hz/24Hz Refresh Rates and Auto Lip-Sync compensation

Advanced Features

- New SCENE buttons (BD/DVD, TV, CD and Radio) quick and simple to use
- YPAO sound optimisation for automatic speaker setup
- iPod compatibility via optional YDS-11 Universal Dock
- Bluetooth (A2DP) compatibility with optional Yamaha Bluetooth® Wireless Audio Receiver YBA-10
- On-screen dispaly
- Front panel mini jack for connecting portable audio player
- iPod song titles displayed in English and Western European languages on the front panel and on-screen display
- HDMI CEC functionality
- Initial Volume Setting and Maximum Volume Setting













- Dialogue Lift
- New preset remote unit

Surround Realism

- CINEMA DSP 3D (17 DSP programmes) with Adaptive DSP Level
- Adaptive DRC (Dynamic Range Control)
- Compressed Music Enhancer
- SILENT CINEMA and Virtual CINEMA DSP
- Audio Delay for adjusting Lip-Sync (0-240ms)

Versatile Zone Control

- Zone 2 on/off and control on front panel
- Remote input/output
- Programmable +12V trigger output

Default Settings for New SCENE Buttons



Easy assignment of new SCENE buttons. First select any input and surround mode, then push a SCENE button more than three seconds.



P10021384ARL-RXV665@NPB

AV Receiver **RX-V665**

Main Specifications

Audio Section			
Minimum RMS Output Power (6 ohm	s, 1 kHz, 0.9% THD)		
Front Channels		90 W + 90 W	
Centre Channel		90 W	
Surround Channels		90 W + 90 W	
Surround Back Channels		90 W + 90 W	
Maximum Power (6 ohms, 1 kHz, 10%	b THD)		
Front L/R Channels		115 W + 115 W	
Centre Channel		115 W	
Surround L/R Channels		115 W + 115 W	
Surround Back Channels		115 W + 115 W	
Innut Consitiuit /Impadance	Phono MM	3.5 mV/47 k-ohms	
Input Sensitivity/Impedance (1 kHz, 100 W/8 ohms)	AV5	200 mV/47 k-ohms	
	Subwoofer	200 mV/47 k-ohms	
	Rec Out	200 mV/1.2 k-ohms	
0	Pre Out (F/C/S/SB)	1 V/1.2 k-ohms	
Output Level/Impedance	Subwoofer	1 V/1.2 k-ohms	
	Zone 2 Out	200 mV/1.2 k-ohms	

Dynamic Power/Channel (Front, 6/4/2 ohms)		100/110/125 W	
Frequency Response (AV5, Front)		10 Hz-100 kHz +0, -3 dB	
Total Harmonic Distortion (AV5, Rec Out, Front Sp Out)		0.06% (1 kHz, 50 W/8 ohms)	
Signal-to-Noise Ratio (AV5, 250 mV)		100 dB	
Video Section			
Video Monitor Out Frequency Response C omponent Video Signal		5 Hz-60 MHz -3 dB	
FM 50dB Quieting Sensitivity	Mono	3 μV (20.8 dBf)	
FM Signal-to-Noise Ratio	Mono	74 dB	
	Stereo	69 dB	
General			
Dimensions (W x H x D)		435 x 151 x 364 mm	
Weight		8.5 kg	

YDS-11 Universal Dock for iPod

The optional YDS-11 Universal Dock lets you connect your iPod to the receiver.

iPod not included



Made for Made forPod

Yamaha Bluetooth® Wireless Audio Receiver

The optional YBA-10 Bluetooth Wireless Audio Receiver docks to the receiver and supports A2DP audio streaming, so users can enjoy music wirelessly from Bluetooth-enabled mobile phones, Windows PCs and Macs.





Extensive Connections

Inputs	
HDMI	4
Radio Antenna (FM/AM)	1 / 1
Dock Terminal for Optional Dock Accessories	1
Optical Digital (Fixed)	2
Coaxial Digital (Fixed)	2
S-Video	1
Analogue Audio*	5
Component Video (Fixed)	2
Multi-Channel External Decoder	8ch

^{*} Including front panel terminals.

Outputs	
HDMI	1
Analogue Audio	2
Pre Out	7ch
Component Video Monitor	1
Composite Monitor	1
Composite AV	1
Speaker (without subwoofer)* / **	7ch / 9 ter.
Subwoofer	1

^{*} Assignable for surround back L/R to bi-amp (front L/R).

^{**} Banana-plug compatible speaker terminals are not available in some areas.

Others Zone 2 Audio Out Remote In/Out 1/1 +12V/15mA Trigger Out

[•] iPod is a trademark of Apple Inc., registered in the US. and other countries. • The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. • Dolby and the double-D symbol are registered trademarks of Dolby Laboratories. • DTS is a registered trademark and the DTS logos, Symbol, DTS-HD and DTS-HD Master Audio are trademark of DTS, Inc. • HDMI, the HDMI logo and High-Definition Multimedia Interface are trademarks or registered trademarks of HDMI Licensing LtC. • Burr-Brown products are trademarks of Texas Instruments, Inc. • "xxxColour" is a trademark of Sony Corporation. • CINEMA DSP is a trademark of Yamaha Corporation. • SILENT CINEMA is a trademark of Yamaha Corporation. • Product designs and specifications are subject to change without notice.