Supports HD audio and video sources, 8 in/2 out HDMI (V.1.4a with 3D and Audio Return Channel), HD Audio decoding with CINEMA DSP 3D, new GUI, new YPAO, network functions, and control via web browser.











Oil-Damped Hidden Control Panel Includes Usb Port, Aux Input Terminals, Zone 2 Switch, YPAO Optimised Microphone Jack, And More.





















High Sound Quality

- 7-channel powerful surround sound (735W=105W x 7 RMS, 1,015W=145W x 7 max)
- HD Audio format decoding: Dolby TrueHD and DTS-HD Master Audio; Dolby Digital Plus and DTS-HD High Resolution Audio
- Symmetrical power amplifier layout
- New heat sink with anti-vibration and anti-thermal properties
- · Rigid chassis with additional bottom frames
- · High speed thermal feedback power amplifier
- DAC on Pure Ground circuitry with high quality Burr-Brown DACs
- Ultra Low Jitter PLL circuitry
 Intelligent Assignable amplifiers for bi-amp or Surround Back <-> Front Presence or Zone 2 connection

High Picture Quality

- Analogue and HDMI video upscaling to full HD 1080p
- 1080p-compatible HDMI: 8 inputs (1 on front) and 2 outputs (simultaneous)
- Supports Deep Colour (30/36 bit), x.v.Colour, 24Hz Refresh Rate and Auto Lip-Sync compensation
- High quality video processing with precise deinterlacing:
 - -Motion adaptive and edge adaptive deinterlacing -Multi-cadence (incl. 3-2 pull-down) detection

Advanced Features

- New SCENE PLUS simple and versatile functionality
 -12 SCENE buttons (4 on front panel and others on GUI)
- -Zone SCENE 4 SCENE buttons for each Zone -Versatile parameters can be stored into each SCENE
- HDMI (V.1.4a with 3D and Audio Return Channel)
- HDMI CEC functionality
- Network functions
 - -Access to Internet Radio (MP3/WMA) and music files on PC (WAV, MP3, WMA, AAC, FLAC 96/24)
 - -Web Browser Control via PC or PDA
 - -Receiver Manager through network connection
 - -DLNA 1.5 certified
- YPAO sound optimisation with multi-point measurement

New on-screen display GUI with album art and 6 languages (English, French,

- German, Spanish, Russian and Japanese) Flexiblly assignable component video and optical/coaxial (except Video Aux) inputs allow use of a wide range of source components
- Ability to change HDMI input while in Standby Through mode
- USB port for portable audio players and flash drives (MTP/MSC)
- iPod/iPhone compatibility with optional YDS-12 Universal Dock
- iPod song titles displayed in English and Western European languages on the front panel and on-screen display
- Wireless connection for iPod/iPhone with optional YID-W10
- Bluetooth (A2DP) compatibility with optional Yamaha Bluetooth® Wireless Audio
- Dialogue Lift
- Auto power down function with variable time setting
- Preset remote unit

Surround Realism

- HD Audio decoding with CINEMA DSP 3D (17 DSP programmes)
- Compressed Music Enhancer with CINEMA DSP
- Virtual Presence Speaker function for CINEMA DSP 3D surround without Front Presence Speakers
- Channel expandability with external amplifier (7 channel expandability (bi-amping))
- Adaptive DRC (Dynamic Range Control) and Adaptive DSP Level

Versatile Zone Control

- Zone 2 on/off and control on front panel
- Zone video assign (Zone 2)System Backup / Recovery function
- Multi-channel output in main Zone plus 2-channel HDMI output in a second Zone
- Zone MONO, Zone volume and tone controls
- Party mode

AV Receiver RX-V1067

Main Specifications

main precincutions			
Minimum RMS Output Power (8 ohms, 20 Hz–20 kHz) (0.06% THD)	Front Channels	105 W + 105 W	
	Centre Channel	105 W	
	Surround Channels	105 W + 105 W	
	Surround Back Channels	105 W + 105 W	
I	Front Channels	145 W + 145 W	
Max Power per Channel	Centre Channel	145 W	
(8 ohms, 1 kHz, 10% THD)	Surround Channels	145 W + 145 W	
9	Surround Back Channel	145 W + 145 W	
Dynamic Power/Channel Front L/R, 8	8/6/4/2 ohms)	135/165/210/280 W	
Total Harmonic Distortion (AV1 etc, :	20 Hz-20 kHz, Front L/R)	0.04% (55 W/8 ohms)	
	Phono MM	3.5 mV/47 k-ohms	
Input Sensitivity/Impedance	Audio 2, etc	200 mV/47 k-ohms	
(1 kHz, 100 W/8 ohms, Multi-0	Ch In) F/C/S/SB	200 mV/47 k-ohms	
	Subwoofer	200 mV/47 k-ohms	

	AV Out	200 mV/1.2 k-ohms
	Headphone Out	150 mV/100 ohms
Output Level/Impedance	Pre Out (F/C/S/SB)	1 V/1.2 k-ohms
	Subwoofer	1 V/1.2 k-ohms
	Zone 2 Out	1 V/1.2 k-ohms
Frequency Response (Audio 2 etc, Pure Direct, Front L/R)		10 Hz-100 kHz +0, -3 dB
Signal-to-Noise Ratio (Audio 2 etc, Input Shorted, Sp Out)		100 dB (250 mV)
Video Monitor Out Frequency Response Component Video Signal		5 Hz-100 MHz ±3 dB
FM 50dB Quieting Sensitivity	Mono	3 μV (20.8 dBf)
FM Signal-to-Noise Ratio	Mono / Stereo	74 dB / 70 dB
Standby Power Consumption (HDMI Off/Standby Through Off)		0.2 W
Standby Power Consumption (HDMI On/Standby Through On)		2.7 W
Standby Power Consumption (NET Standby On)		4.5 W
Dimensions (W x H x D)		435 x x 182 x 430 mm
Weight		14.7 kg

YDS-12 Universal Dock for iPod/iPhone

The optional YDS-12 Universal Dock lets you connect your iPod or iPhone to the receiver.

iPod [iPhone



YID-W10 Wireless Dock System for iPod/iPhone

The optional YID-W10 ensures that you enjoy maximum sound quality and no lip sync (AV matching) problems.





Yamaha Bluetooth® Wireless Audio Receiver

The optional YBA-10 supports A2DP audio streaming, enjoying music wirelessly from Bluetooth-enabled mobile phones, Windows PCs and





ODOK- ON THE WORK IN THE PROPERTY OF THE PROPE	AV 2 AV 2 AV 3 AV 4 AV 5 AV 5 AV 5	N7 € (S) N7
PHONO GNO CON ZONE COT AND	PP COMPONENT VICEO 3 Pp	OUT WYAMAHA MODEL NO. RX-V1067
	MULTICH INPUT CONTROL ZONE OUT PRE OUT (SMOLE)	+IEVO JAMAX
O COMM O	FRONT SERIOUS DE BLOC SERVOSTES TO SE SUR SUR SUR DE ANCE SERVOS DE BLOC SERVOS D	FRONT O @ ZONES/. O AC IN
PRONT 40 MM FRONT OTHERS 60 MM OTHERS	- MR : BOMM, NR : BOMM	
CAUTION RISK OF RECEPTOR SHOWN	SINGLE	ESTRA SU

Extensive Connections

Extensive Connections	
Inputs	
HDMI*1	8
USB*1	1
Network	1
Radio Antenna (FM/AM)	1 / 1
Dock Terminal for Optional Dock Accessories	1
Optical Digital (Assignable except Video AUX)*1	4
Coaxial Digital (Assignable)	3
Analogue AV*1 / Audio (with Phono)	5 / 5
Component Video (Assignable)	4
Composite / S-Video*1 Monitor	5 / 5
Multi-Channel External Decoder	8ch

^{*1} Including front panel terminals.

Outputs	
HDMI	2 (simultaneous)
Optical Digital	1
Analogue Audio	1
Pre Out	7ch
Component Video Monitor*2	1
Composite Monitor*2 / S-Video*2	1 / 1
AV Out (Composite / S-Video)	1 / 1
Speaker (without subwoofer)*3	7ch
Extra Speaker (Front Presence / Zone 2)	2ch*4
Subwoofer	2 x mono
*2 Assignable to maiter out or Zone out	

Assignable to moitor out or Zone out.

Remote In/Out*5

Zone 2 Audio Out with Volume/Tone Control

P10022766ARL-RXV1067@NPB

^{*3} Banana-plug compatible speaker terminals are not available in ** Power amplifier assignable: Surround Back to Front

Presence/Zone 2.

⁺¹²V/150 mA Dual Trigger Out*6 RS-232C Terminal for Detachable Power Cable

^{*5} SCENE-IR support

^{*6} Yamaha subwoofer system control support

^{• &}quot;Made for iPod," and "Made for iPhone" mean that an electronic accessory has been designed to connect specifically to iPod or iPhone respectively, and has been certified by the developer to meet Apple performance standards. Apple is not responsible for the operation of this device or its compliance with safety and regulatory standards iPhone, iPod, iPod classic, iPod nano, and iPod touch are trademarks of Apple Inc. registered in the U.S. and other countries. • The Bluetooth® word mark and logos are registered trademarks on word by Bluetooth SIG, Inc. • Dolby and the double-D symbol are registered trademarks of Dolby Laboratories. • DTS is a registered trademark and the DTS logos, Symbol, (DTS-HD and DTS-HD Master Audio are trademark of DTS, inc. • HDMI, the HDMI logo and High-Definition • Windows is a registered trademark of Microsoft Corporation in the United States and other countries. • DUNA certified is a trademark of the Digital Living Network Alliance. • Burn-Brown products are trademarks of Texas Instruments, Inc. • "x.v.Colour" is a trademark • CINEMA DSP is a trademark of Yamaha Corporation. • Product designs and specifications are subject to change without notice.