

Top video and audio quality, with 1080p/24Hz-compatible HDMI video output, full HD Audio decoding and 7.1-channel audio output. Also supports BD-Live and BonusView, and matches Yamaha AV receivers.



BONUSVIEW™

BD-Video



AVCHD™

 HDMI™
HIGH DEFINITION MULTIMEDIA INTERFACE


JPEG

Supports BD-Live and BonusView

- Connect to the internet to access the fun and informative features that BD-Live provides
- Secondary Video/Audio for enhanced commentary and information
- Virtual Package for new entertainment possibilities with USB memory

Magnificent Audio Performance

- For all HD formats:
 - Direct bitstream and multi-channel Linear PCM output via HDMI
 - Analogue 7.1 multi-channel output with 4 x 2-channel DACs
 - Analogue down-mixed 2-channel output
- 192kHz/24-bit audio DAC
- Terminal for detachable power cable


High Picture Quality

- 1080p/24Hz-compatible HDMI video output
- x.v.Colour and Deep Colour compatibility
- 1080p playback for DVDs, photos and personal video data

Advanced Facilities

- Yamaha SCENE compatibility
- HDMI CEC functionality
- On-screen display GUI
- IR In/Out ports
- Extensive disc/format compatibility
- Dynamic Range Compression
- 3 dimmer modes



 **Brilliant Audio: Titanium**
 Titanium finish available in some areas.

Blu-ray Disc Player BD-S1065

NEW PRODUCT BULLETIN



Main Specifications

Disc/Format Compatibility	BD-Video, BD-R (BD Video), BD-RE (BD-Video), DVD-Video, DVD-R/RW (DVD-Video, DVD-VR, AVCHD), DVD+R/RW (+VR, AVCHD), CD and CD-R/RW (CD-DA, JPEG)
---------------------------	--

VIDEO PERFORMANCE

Video Output	1 Vp-p/75 ohms
S-Video Output	Y 1 Vp-p/75 ohms
	C 0.3 Vp-p/75 ohms (PAL); 0.286 Vp-p/75 ohms (NTSC)
Component Video Output	Y 1 Vp-p/75 ohms
	Pb 0.7 Vp-p/75 ohms
	Pr 0.7 Vp-p/75 ohms
HDMI Output	480p (576p)/720p/1080i/1080p/1080p@24 Hz

AUDIO PERFORMANCE

Output Level (1 kHz, 0 dB)	2 ± 0.3 V (BD/DVD/CD-DA)
Signal-to-Noise Ratio	115 dB (BD/DVD/CD-DA)
Dynamic Range	105 dB (BD/DVD)
	100 dB (CD-DA)
Harmonic Distortion	0.0028% (BD/DVD)
	0.003% (CD-DA)
Frequency Response	2 Hz-20 kHz (CD-DA)
	2 Hz-22 kHz (BD/DVD 48 kHz sampling) 2 Hz-44 kHz (BD/DVD 96 kHz sampling)

GENERAL

Standby Power Consumption	1 W
Dimensions (W x H x D)	435 x 96 x 316 mm
	17-1/8" x 3-3/4" x 12-1/2"
Weight	4.5 kg; 9.9 lbs.



Extensive Connections

HDMI Output	1	S-Video / Composite Video Output	1 / 1
USB Port	1	7.1-Channel Discrete Audio Output	1
Ethernet	1	Mixed 2-Channel Audio Output	1
Digital Audio Output (Optical / Coaxial)	1 / 1	Remote Control IR Code Input / Output	1 / 1
Component Video Output (Progressive/Interlace)	1	Terminal for Detachable Power Cable	1

• Java and all Java-based trademarks and logos are trademarks or registered trademarks of Sun Microsystems, Inc. in the United States and other countries. • Dolby and the double-D symbol are trademarks of Dolby Laboratories. • DTS is a registered trademark & the DTS logos and Symbol are trademarks of DTS, Inc. • HDMI, the HDMI logo and High-Definition Multimedia Interface are trademarks or registered trademarks of HDMI Licensing LLC. • "x.v.Colour" is a trademark of Sony Corporation. • "AVCHD" and the "AVCHD" logo are trademarks of Matsushita Electric Industrial Co., Ltd. and Sony Corporation. • Products designs and specifications are subject to change without notice.